

# Fiber Optic Patch Cords



## Product Description

Fiber optic patch cords are installed for connections to the active devices on the panels dealers and for connections to workstations wall outlets.

All hoses are supplied with covers LSZH-FR and are 100% tested for ensure strict compliance with the TIA/EIA 568.B-2, ISO11801 Ed2, EN50173-1 y Telecordia GR326-CORE.

The hoses are available with all industry-standard connectors:

|     |         |
|-----|---------|
| SC  | SC/APC  |
| FC  | FC/APC  |
| LC  | LC/APC  |
| E-2 | E-2/APC |
| ST  |         |
| MU  |         |

Also with all types of cables (simplex, duplex ZIP, duplex and multiple fiber FLAT) and existing fiber (OM1, OM2, OM3, OS1).

For other configurations and models call our sales department.

## Multimode Specifications 62.5 / 125

Length: 1,2,3,5,10 and 15 meters  
Return loss (typical) > = 25dB  
Insertion loss (typical) <0.15 dB  
Temperature range: -40 to +60 ° C  
Zirconium ceramic ferrule  
3mm orange cover



## Technical Specifications Singlemode 9/125

Length: 1,2,3,5,10 and 15 meters  
Return loss (typical) > = 55dB  
Insertion loss (typical) <0.2 dB  
Temperature range: -40 to +80 ° C  
Zirconium ceramic ferrule  
3mm yellow cap



\* Center Cable reserves the right to modify or change specifications without notice

Center Cable,s.l.  
C/Camino del Barranco 4 y 6 P.I.Las Arenas de Pinto  
28320-Pinto-MADRID

C.I.F.: B-82548611  
Telf.: 91-692 60 30 Fax.: 91-692 64 28

