




## Clic clamp for RADIAFLEX® 1 5/8"

**Product Description**

Clic Clamp, 1-5/8" RADIAFLEX polyamide black, halogen free  
fire class UL94HB

**Features/Benefits**

Safe and efficient installation of RADIAFLEX® cable with clic-clamps. Simple mounting by using wall plugs and screws. Simply push in by hand, clamp will grip and lock by applying slight pressure.

**Technical Specifications**

Product Line	Radiating Cable Accessories
Product Type	Hanger
Hanger Type	Clic clamp
Transmission Line Type	RLF* RLK* RLV* RAY*158-50*A RCF158-50*A
Cable Type	Radiating Cable
Cable Size	1-5/8"
Number of Cable / Waveguide Runs	1
Color	Black
Material	Polyamide
Fire Class	UL94 HB
Installation Temperature, °C(°F)	-20 to 80 (-4 to 176 )
Operation Temperature, °C(°F)	-50 to 85 (-58 to 185 )
Storage Temperature, °C(°F)	-50 to 85 (-58 to 185 )
Package Quantity	50

**Notes**

\* valid for all cable versions

**Other Documentation**

All information contained in the present datasheet is subject to confirmation at time of ordering

Clic clamp for RADIAFLEX® 1 5/8"

